



- Notes:
1. RoHS Compliant;
 2. Hole: $\text{Ø}6.0 \pm 0.08\text{mm}$;
Panel Thickness: 0.8-2.0mm.

Part No.	Article No.	Part No.	Article No.	A	D Bundle Dia.
61378	GSOTL6-45-4M-V0	60955	GSOTL6-45-4M-66	4.0	10.2-12.7
61377	GSOTL6-45-1-V0	60956	GSOTL6-45-1-66	4.8	
61379	GSOTL6-45-2-V0	60957	GSOTL6-45-2-66	12.7	
61380	GSOTL6-45-3-V0	60958	GSOTL6-45-3-66	19.1	
61381	GSOTL6-45-4-V0	60959	GSOTL6-45-4-66	25.4	
61382	GSOTL6-45-5-V0	60960	GSOTL6-45-5-66	31.8	
Material: PA66 UL94V0 Color: Natural		Material: PA66 UL94V2 Color: Natural			

Americom GmbH
<https://americom.de>



DATE 2022-6-15 DIMENSION TOLERANCE

TITLE	STAND-OFF TWIST LOCK					SCALE	FIT	$L \leq 4$	± 0.10
ARTICLE NO.	GSOTL6-45	MOLD NO.	S0636	DRAW	JF	UNIT	MM	$4 < L \leq 15$	± 0.20
PART NO.	SEE TABLE	MATERIAL	SEE TABLE	DESIGN	JF	VERSION	A0	$15 < L \leq 50$	± 0.30
DWG NO.	E6267	COLOR	SEE TABLE	APPROVAL	FDL	VIEW		$50 < L \leq 100$	± 0.40